

Package: VectorForgeML (via r-universe)

June 5, 2026

Type Package

Title High-Performance Machine Learning Framework with C++ Acceleration

Version 0.1.0

Description Machine learning utilities for fast vectorized model training. Methods are based on standard statistical learning references such as Hastie et al. (2009) [<doi:10.1007/978-0-387-84858-7>](https://doi.org/10.1007/978-0-387-84858-7).

License Apache License (>= 2)

Encoding UTF-8

Depends R (>= 3.5.0)

Imports methods, Rcpp

LinkingTo Rcpp

SystemRequirements OpenMP (optional)

URL <https://vectorforgeml.work.gd>

BugReports <https://github.com/mohd-musheer/VectorForgeML/issues>

NeedsCompilation yes

RoxygenNote 7.3.3

Repository <https://mohd-musheer.r-universe.dev>

Date/Publication 2026-06-05 05:40:39 UTC

RemoteUrl <https://github.com/mohd-musheer/vectorforgeml>

RemoteRef HEAD

RemoteSha 4fab6b3f118b7051ec04c6de5601f4f001acfc5f

Contents

accuracy_score	2
ColumnTransformer-class	3
confusion_matrix	4

confusion_stats	4
DecisionTree-class	5
drop_constant_columns	6
f1_score	6
find_best_k	7
fit_linear_model	8
KMeans-class	9
KNN-class	9
LabelEncoder-class	10
LinearRegression-class	10
LogisticRegression-class	11
macro_f1	12
macro_precision	12
macro_recall	13
MinMaxScaler-class	14
mse	14
OneHotEncoder-class	15
PCA-class	15
Pipeline-class	16
plot_confusion_matrix	17
precision_score	17
predict_linear_model	18
r2_score	19
RandomForest-class	20
recall_score	20
RidgeRegression-class	21
rmse	22
SoftmaxRegression-class	22
StandardScaler-class	23
train_test_split	24

Index **25**

accuracy_score	<i>Accuracy Score</i>
----------------	-----------------------

Description

Computes classification accuracy.

Usage

```
accuracy_score(y_true, y_pred)
```

Arguments

y_true	true labels
y_pred	predicted labels

Details

Provides functionality for `accuracy_score` operations.

Value

numeric accuracy

See Also

[VectorForgeML-package](#)

Examples

```
y_true <- c(1,0,1,1)
y_pred <- c(1,0,0,1)
accuracy_score(y_true, y_pred)
```

ColumnTransformer-class

Column Transformer

Description

Applies transformations to specific columns.

Details

Provides functionality for ColumnTransformer operations.

Value

ColumnTransformer object

See Also

[VectorForgeML-package](#)

Examples

```
model <- ColumnTransformer$new(num_cols="A", cat_cols="B")
```

confusion_matrix *Confusion Matrix*

Description

Computes confusion matrix.

Usage

```
confusion_matrix(y_true, y_pred)
```

Arguments

y_true	true labels
y_pred	predicted labels

Details

Provides functionality for confusion_matrix operations.

Value

matrix

See Also

[VectorForgeML-package](#)

Examples

```
y_true <- c(1,0,1,1)
y_pred <- c(1,0,0,1)
confusion_matrix(y_true, y_pred)
```

confusion_stats *Confusion Matrix Statistics*

Description

Calculates accuracy, precision, recall, F1 from confusion matrix.

Usage

```
confusion_stats(cm)
```

Arguments

cm confusion matrix

Details

Provides functionality for confusion_stats operations.

Value

list

See Also

[VectorForgeML-package](#)

Examples

```
cm <- matrix(c(10, 2, 1, 15), nrow=2)
try({ confusion_stats(cm) })
```

DecisionTree-class *Decision Tree Model*

Description

Tree-based classification/regression algorithm.

Details

Provides functionality for DecisionTree operations.

Value

DecisionTree object

See Also

[VectorForgeML-package](#)

Examples

```
model <- DecisionTree$new()
X <- matrix(rnorm(20), nrow=10)
y <- sample(0:1, 10, replace=TRUE)
model$fit(X,y)
model$predict(X)
```

drop_constant_columns *Drop Constant Columns*

Description

Removes columns with zero variance.

Usage

```
drop_constant_columns(X, eps = 1e-12)
```

Arguments

X	input matrix/dataframe
eps	for param eps

Details

Provides functionality for drop_constant_columns operations.

Value

cleaned matrix

See Also

[VectorForgeML-package](#)

Examples

```
x <- data.frame(a=c(1,1,1), b=c(1,2,3))
drop_constant_columns(x)
```

f1_score

F1 Score

Description

Harmonic mean of precision and recall.

Usage

```
f1_score(y_true, y_pred, positive = NULL)
```

Arguments

y_true	true labels
y_pred	predicted labels
positive	positive class label

Details

Provides functionality for f1_score operations.

Value

numeric f1 score

See Also

[VectorForgeML-package](#)

Examples

```
y_true <- c(1,0,1,1)
y_pred <- c(1,0,0,1)
f1_score(y_true, y_pred)
```

find_best_k

Find Best K

Description

Finds optimal K value for KNN.

Usage

```
find_best_k(X, y, k_values = seq(1, 15, 2))
```

Arguments

X	features
y	labels
k_values	for k value

Details

Provides functionality for find_best_k operations.

Value

numeric best k

See Also

[VectorForgeML-package](#)

Examples

```
x <- matrix(rnorm(200), nrow=100)
y <- sample(0:1, 100, replace=TRUE)
find_best_k(x, y, k_values=c(1,3,5))
```

fit_linear_model	<i>Fit Linear Model (Fast C++ backend)</i>
------------------	--

Description

Internal helper for linear regression training.

Usage

```
fit_linear_model(X, y)
```

Arguments

X	numeric matrix
y	numeric vector

Details

Provides functionality for fit_linear_model operations.

Value

model object

See Also

[VectorForgeML-package](#)

Examples

```
X <- matrix(rnorm(20), nrow=10)
y <- rnorm(10)
try({ fit_linear_model(X, y) })
```

KMeans-class

KMeans Clustering

Description

Unsupervised clustering algorithm.

Details

Provides functionality for KMeans operations.

Value

KMeans object

See Also

[VectorForgeML-package](#)

Examples

```
x <- matrix(rnorm(20), nrow=10)
model <- KMeans$new()
model$fit(x)
```

KNN-class

K-Nearest Neighbors Model

Description

Instance-based learning algorithm.

Details

Provides functionality for KNN operations.

Value

KNN object

See Also

[VectorForgeML-package](#)

Examples

```
model <- KNN$new(k=3, mode="classification")
X <- matrix(rnorm(20), nrow=10)
y <- sample(0:1, 10, replace=TRUE)
model$fit(X,y)
model$predict(X)
```

LabelEncoder-class *Label Encoder*

Description

Converts categorical labels into numeric values.

Details

Provides functionality for LabelEncoder operations.

Value

LabelEncoder object

See Also

[VectorForgeML-package](#)

Examples

```
enc <- LabelEncoder$new()
x <- c("a", "b", "a")
enc$fit(x)
enc$transform(x)
```

LinearRegression-class
Linear Regression Model

Description

Fast linear regression implemented in C++ backend.

Details

Provides functionality for LinearRegression operations.

Value

LinearRegression object

See Also

[VectorForgeML-package](#)

Examples

```
model <- LinearRegression$new()
X <- matrix(rnorm(100),50,2)
y <- rnorm(50)
model$fit(X,y)
model$predict(X)
```

LogisticRegression-class

Logistic Regression Model

Description

Binary classification logistic regression.

Details

Provides functionality for LogisticRegression operations.

Value

LogisticRegression object

See Also

[VectorForgeML-package](#)

Examples

```
model <- LogisticRegression$new()
X <- matrix(rnorm(20), nrow=10)
y <- sample(0:1, 10, replace=TRUE)
model$fit(X,y)
model$predict(X)
```

macro_f1

Macro Precision

Description

Computes macro-averaged precision.

Usage

```
macro_f1(y_true, y_pred)
```

Arguments

y_true	true labels
y_pred	predicted labels

Details

Provides functionality for macro_f1 operations.

Value

numeric score

See Also

[VectorForgeML-package](#)

macro_precision

Macro Precision

Description

Computes macro-averaged precision.

Usage

```
macro_precision(y_true, y_pred)
```

Arguments

y_true	true labels
y_pred	predicted labels

Details

Provides functionality for macro_precision operations.

Value

numeric score

See Also

[VectorForgeML-package](#)

macro_recall	<i>Macro Precision</i>
--------------	------------------------

Description

Computes macro-averaged precision.

Usage

```
macro_recall(y_true, y_pred)
```

Arguments

y_true	true labels
y_pred	predicted labels

Details

Provides functionality for macro_recall operations.

Value

numeric score

See Also

[VectorForgeML-package](#)

MinMaxScaler-class *Standard Scaler*

Description

Standardizes features by removing mean and scaling to unit variance.

Details

Provides functionality for MinMaxScaler operations.

Value

StandardScaler object

See Also

[VectorForgeML-package](#)

Examples

```
s <- MinMaxScaler$new()
x <- matrix(rnorm(20), nrow=10)
s$fit(x)
s$transform(x)
```

mse *Mean Squared Error*

Description

Calculates regression error.

Usage

```
mse(y_true, y_pred)
```

Arguments

y_true	true values
y_pred	predicted values

Details

Provides functionality for mse operations.

Value

numeric mse

See Also

[VectorForgeML-package](#)

OneHotEncoder-class *One Hot Encoder*

Description

Converts categorical variables into binary vectors.

Details

Provides functionality for OneHotEncoder operations.

Value

OneHotEncoder object

See Also

[VectorForgeML-package](#)

Examples

```
enc <- OneHotEncoder$new()
df <- data.frame(a=c("x", "y", "x"))
enc$fit(df)
enc$transform(df)
```

PCA-class *Principal Component Analysis*

Description

Dimensionality reduction technique.

Details

Provides functionality for PCA operations.

Value

PCA object

See Also

[VectorForgeML-package](#)

Examples

```
model <- PCA$new(n_components=2)
X <- matrix(rnorm(30), nrow=10)
model$fit(X)
model$transform(X)
```

Pipeline-class

Pipeline

Description

Chains preprocessing and model steps.

Details

Provides functionality for Pipeline operations.

Value

Pipeline object

See Also

[VectorForgeML-package](#)

Examples

```
model <- Pipeline$new(list(StandardScaler$new()))
```

plot_confusion_matrix *Plot Confusion Matrix*

Description

Visualizes confusion matrix.

Usage

```
plot_confusion_matrix(cm, normalize = TRUE)
```

Arguments

cm	confusion matrix
normalize	Normlize

Details

Provides functionality for plot_confusion_matrix operations.

Value

plot

See Also

[VectorForgeML-package](#)

Examples

```
cm <- matrix(c(10, 2, 1, 15), nrow=2)
try({ plot_confusion_matrix(cm) })
```

precision_score *Precision Score*

Description

Computes precision metric.

Usage

```
precision_score(y_true, y_pred, positive = NULL)
```

Arguments

y_true	true labels
y_pred	predicted labels
positive	positive class label

Details

Provides functionality for precision_score operations.

Value

numeric precision

See Also

[VectorForgeML-package](#)

Examples

```
y_true <- c(1,0,1,1)
y_pred <- c(1,0,0,1)
precision_score(y_true, y_pred)
```

predict_linear_model *Predict Linear Model*

Description

Predict values using trained linear model.

Usage

```
predict_linear_model(model, X)
```

Arguments

model	trained model
X	matrix

Details

Provides functionality for predict_linear_model operations.

Value

numeric vector

See Also

[VectorForgeML-package](#)

Examples

```
X <- matrix(rnorm(20), nrow=10)
y <- rnorm(10)
model <- fit_linear_model(X, y)
predict_linear_model(model, X)
```

r2_score

R2 Score

Description

Coefficient of determination.

Usage

```
r2_score(y_true, y_pred)
```

Arguments

y_true	true values
y_pred	predicted values

Details

Provides functionality for r2_score operations.

Value

numeric r2 score

See Also

[VectorForgeML-package](#)

RandomForest-class *Random Forest Model*

Description

Ensemble of decision trees.

Details

Provides functionality for RandomForest operations.

Value

RandomForest object

See Also

[VectorForgeML-package](#)

Examples

```
model <- RandomForest$new(ntrees=5)
X <- matrix(rnorm(20), nrow=10)
y <- sample(0:1, 10, replace=TRUE)
model$fit(X,y)
model$predict(X)
```

recall_score *Recall Score*

Description

Computes recall metric.

Usage

```
recall_score(y_true, y_pred, positive = NULL)
```

Arguments

y_true	true labels
y_pred	predicted labels
positive	positive class label

Details

Provides functionality for recall_score operations.

Value

numeric recall

See Also

[VectorForgeML-package](#)

Examples

```
y_true <- c(1,0,1,1)
y_pred <- c(1,0,0,1)
recall_score(y_true, y_pred)
```

RidgeRegression-class *Ridge Regression Model*

Description

Linear regression with L2 regularization.

Details

Provides functionality for RidgeRegression operations.

Value

RidgeRegression object

See Also

[VectorForgeML-package](#)

Examples

```
model <- RidgeRegression$new()
X <- matrix(rnorm(20), nrow=10)
y <- rnorm(10)
model$fit(X,y,lambda=1.0)
model$predict(X)
```

rmse *Root Mean Squared Error*

Description

Square root of MSE.

Usage

```
rmse(y_true, y_pred)
```

Arguments

y_true	true values
y_pred	predicted values

Details

Provides functionality for rmse operations.

Value

numeric rmse

See Also

[VectorForgeML-package](#)

SoftmaxRegression-class
Softmax Regression Model

Description

Multiclass logistic regression.

Details

Provides functionality for SoftmaxRegression operations.

Value

SoftmaxRegression object

See Also

[VectorForgeML-package](#)

Examples

```
model <- SoftmaxRegression$new()
X <- matrix(rnorm(20), nrow=10)
y <- sample(0:2, 10, replace=TRUE)
model$fit(X,y)
model$predict(X)
```

StandardScaler-class *Drop Constant Columns*

Description

Removes columns with zero variance.

Arguments

X input matrix/dataframe

Details

Provides functionality for StandardScaler operations.

Value

cleaned matrix

See Also

[VectorForgeML-package](#)

Examples

```
s <- StandardScaler$new()
x <- matrix(rnorm(20), nrow=10)
s$fit(x)
s$transform(x)
```

train_test_split *Train Test Split*

Description

Splits dataset into training and testing sets.

Usage

```
train_test_split(X, y, test_size = 0.2, seed = NULL)
```

Arguments

X	features
y	labels
test_size	proportion for test set
seed	for random seed

Details

Provides functionality for train_test_split operations.

Value

list

See Also

[VectorForgeML-package](#)

Examples

```
X <- matrix(rnorm(20), nrow=10)
y <- sample(0:1, 10, replace=TRUE)
train_test_split(X, y, test_size=0.2)
```

Index

accuracy_score, 2

ColumnTransformer
(ColumnTransformer-class), 3

ColumnTransformer-class, 3

confusion_matrix, 4

confusion_stats, 4

DecisionTree (DecisionTree-class), 5

DecisionTree-class, 5

drop_constant_columns, 6

f1_score, 6

find_best_k, 7

fit_linear_model, 8

KMeans (KMeans-class), 9

KMeans-class, 9

KNN (KNN-class), 9

KNN-class, 9

LabelEncoder (LabelEncoder-class), 10

LabelEncoder-class, 10

LinearRegression
(LinearRegression-class), 10

LinearRegression-class, 10

LogisticRegression
(LogisticRegression-class), 11

LogisticRegression-class, 11

macro_f1, 12

macro_precision, 12

macro_recall, 13

MinMaxScaler (MinMaxScaler-class), 14

MinMaxScaler-class, 14

mse, 14

OneHotEncoder (OneHotEncoder-class), 15

OneHotEncoder-class, 15

PCA (PCA-class), 15

PCA-class, 15

Pipeline (Pipeline-class), 16

Pipeline-class, 16

plot_confusion_matrix, 17

precision_score, 17

predict_linear_model, 18

r2_score, 19

RandomForest (RandomForest-class), 20

RandomForest-class, 20

recall_score, 20

RidgeRegression
(RidgeRegression-class), 21

RidgeRegression-class, 21

rmse, 22

SoftmaxRegression
(SoftmaxRegression-class), 22

SoftmaxRegression-class, 22

StandardScaler (StandardScaler-class), 23

StandardScaler-class, 23

train_test_split, 24